

■ Features :

- 0.98 typical of power factor
- High reliability and low ripple noise
- Built-in remote sense function
- Built-in remote ON/OFF control
- Built-in power good signal output
- Programmable output voltage
- Forced current sharing at parallel operation
- Output short circuit / over voltage / overload / over temperature protections
- CB, CE, UL, TUV approved



CE  us CB



MODEL		600U-P006	600U-P009	600U-P012	600U-P015	600U-P018	600U-P024	600U-P030	600U-P036	600U-P048	600U-P060
Output	DC Voltage	5V	9V	12V	15V	18V	24V	30V	36V	48V	60V
	Rated Current	80A	66A	50A	40A	33A	25A	20A	16A	12A	13A
	Rated Power	400W	594W	600W	600W	594W	600W	600W	576W	576W	600W
	Ripple & Noise (max.)	150mVp-p	150mVp-p	150mVp-p	150mVp-p	180mVp-p	240mVp-p	300mVp-p	360mVp-p	480mVp-p	600mVp-p
	Voltage Adj. Range	+3% ~ -12% typical adjustment by potentiometer; 20% ~ 100% adjustment by 1 ~ 5VDC external control									
	Line & Load Regulation	Less than 1%									
	Setup, Rise, Hold Time	500ms, 250ms, 12ms at full load									
Input	Voltage Range	180 ~ 260VAC / 260 ~ 370VAC									
	frequency Range	47 ~ 63Hz									
	Power Factor (Typ.)	0.98 / 230VAC									
	Efficiency (Typ.)	78%	83%	84%	85%	85%	88%	88%	88%	89%	90%
	AC Current (Typ.)	3.5A / 230VAC									
	Inrush current (Typ.)	60A / 230VAC									
	Leakage Current (max.)	< 3.5mA / 240VAC									
Protection	Over Load	105 ~ 115% rated output power (Current limiting, delay shot down output voltage, re-power on to recover)									
	Over Voltage	110 ~ 135% follow to output set up point(shut down output voltage, re-power on to recover)									
	Over Temperature	>100°C / measure by heat sink, near transformer (shut down output voltage, recovers automatically after temperature goes down)									
Environment	Working Temp. & Humidity	0 ~ +50°C; @100% Load, +65°C @50% Load; 20% ~ 90% RH non-condensing									
	Storage Temp.& Humidity	-20 ~ +85°C, 10 ~ 95%RH									
	Temp.Coefficint	±0.04% / °C (0 ~ 50°C)									
Safety & EMC	Safety Standards	Meet UL1950, TUV EN60950-1									
	Withstand Voltage	I/P - O/P : 3KVAC; I/P - FG : 1.5KVAC; O/P - FG : 0.5KVAC									
	Isolation Resistance	I/P - O/P, I/P - FG, O/P - FG : 100M Ohms / 500VDC									
	EMI Conduction & Radiation	Meet EN55022 Class A									
	Harmonic Current	Meet EN61000-3-2,3									
	EMS Immunity	Meet EN55024									
Others	Power Good Signal	Open collector N MOSFET									
	Special Function	DC voltage adj., Remote sensing, Remote control, Parallel operation									
	Cooling	Power rating and temperature controlled cooling fan									
	Dimension (L*W*H)(mm)	284x105x63mm (LxWxH)									
	Packing	2.0kg ; 8sets / 18kgs / Carton									